

RANGER 2000



Class Leading Features, Quality, and Design

Your Sprayer Specialist





Standard Features

- 550 Gallon Tank & Frame
- Adjustable Clevis Hitch Drawbar
- Bottom Suction From Deep Sump
- Top Operated Tank Drain
- High Visibility Dry Sight Gauge
- EC-3 Section Electric Controls
- HC Adjustable Axle 60" to 90"
- 11.2 x 38" Tires & Wheels = 28" Clearance
- HARDI Diaphragm Pumps = Positive displacement & Self Priming
- Sturdy 3/8" thick Main Tank - No Tank Baffles for Easy Clean out
- Eagle 45', 50', 60', or 66' Booms With single 20" spaced ISO Mini Drift Nozzles
- In-Line Boom Filters
- Boom Hydraulics
HY = Hyd. Center Lift and Fold (2 outlets required)
- 5 gal. Clean Water Dispenser
- Cyclone Self Cleaning Filter
- SMV Sign
- Work Platform with Foot Step
- Cable & Hose Holder
- Jack Stand with 5,000 lbs. Capacity



HARDI Diaphragm Pump is Standard



Standard 11.2 x 38" Tires
28" Crop Clearance



(optional)
6.5 gal. Turbo Filler



RANGER 2000

Its everything you expect from a HARDI

HARDI North America

1500 W 76th St
Davenport, IA 52806
PH: (563) 386-1730
Fax: (563) 386-1710

337 Sovereign Road
London, ON N6M 1A6
PH: (519) 659-2771
Fax: (519) 659-2821

www.hardi-us.com